

BRKT LX Cellular Gateway DIN-Rail Mounting Brackets





Features & Benefits

- » Versatile side or rear DIN-rail mount orientations
- » 18-gauge steel construction rather than flimsy aluminum extrusions
- » Stainless steel mounting fasteners
- » Rugged powder-coating
- » Backed by a lifetime warranty

Product Description

BRKT GX series brackets mount Sierra Wireless LX60 industrial cellular gateways onto DIN-rail. The BRKT-LX-REAR mounts the device with a forward-facing profile.

Product Variants Specifications

Part Number	Description
BRKT-LX-REAR	BRKT LX series rear-mount DIN-rail mounting bracket for Sierra Wireless LX60 cellular gateways.

Storage/Operating temperature: -40°C to 80°C

Mechanical Construction

Dimensions:

(H x D x W) 3.0" x 0.78" x 5.85"

Mounting Options:

Rear DIN-rail

Weight:

5 oz.

Materials of Construction

Mounting Hardware: 18-gauge powder-coat painted steel

Mounting Screws: Stainless steel

DIN-Rail Clip: Fiberglass reinforced Nylon 66

Warranty

Lifetime warranty on materials and workmanship.

Scope of Delivery and Accessories

DIN-rail bracket, mounting hardware.

Phone: 214-613-0349 | Fax: 866-622-4068 | www.dinspace.com